



cCharger - the smart charging station

Simple and compact, the most beautiful way to charge.



Easy. Clever. Compact.

Our aim is to make charging as easy and efficient as possible for electric car drivers.

Designation	cCharger Pro
 Voltage	AC: 230V (1 phased) / 400V (3 phased)
Electricity	6A to 16A (32A under development)
Performance	1,4kW to 11kW AC (22kW under development)
 Electrical protection	RCD DC 6mA, AC/DC 30mA
Mechanical protection	IP65 (under review)
Safety standards	IEC 62752, 62196, 61851 - Mode 2/3, EMV, CE (under review)
 Plug on input side	Simple replacement with plug monitoring
 WiFi	inklusive
WiFi Standards	IEEE 802.11 b/g/n
WiFi Frequency	2.4 Ghz
 Bluetooth LE	inklusive
Bluetooth LE Standards	Bluetooth 5 Bluetooth mesh

Designation

cCharger Pro



Mobile LTE Standard

Cat 1

Mobile Download

10 Mbps

Mobile Upload

5 Mbps

Mobile Frequency (4G/2G)

Europa:
LTE FDD: B1/B3/B5/B7/B8/B20/B28
GSM: 850/900/1800/1900 MHz



Display

Capacitive Touchscreen